

1955 Crown Victoria, 2 dr hardtop, convertible door seal Installation



NOTE: It is necessary to use a weather stripping adhesive to install door seals. Dennis Carpenter Ford Reproductions recommends and sells 3M brand Weather Stripping Adhesive. Our part # is COAZ-19554-A

Experience has shown us that taping the door seal into position before any adhesive is applied allows you to check the fit of the seal and also aides in applying the seal.

Apply the adhesive to the door, not the seal. Glue around the door as described.

The best (and cleanest) results comes from adhering a short section of the door seal at a time by removing the securing tape, applying the glue and positioning the the door seal, reapplying the tape then continuing. After the adhesive has cured the securing tape can be removed.

Remember that new door seals are more resilient to compression and will cause your doors to close tightly.



4140 Concord Parkway So., Concord, NC 28027
(704) 786-8139 email: info@dennis-carpenter.com
www.dennis-carpenter.com

TO INSTALL DOOR SEALS

Instructions describe passenger side door seal installation. Part numbers are molded into rubber parts for reference.

Remove the old door seals and residue from the doors. Clean the doors where the seals are to be adhered with a degreaser/wax remover solution.

1. Apply adhesive to molded rubber seal piece B5A-6420530-A and attach to the upper rear of the door

2. Apply the long door seal by starting at the top front of the vent window frame. Apply adhesive to rubber seal B5A-7621382 ("L" shaped) and attach to the top front of the vent window frame. Continue glueing seal down the vent window frame, along the dog leg section then down the hinge side of the door to the front bottom corner.

3. Continue glueing the seal along the bottom of the door to the rear corner the up the latch side of the door.

4. Bring the seal up to the molded rubber seal B5A-6420530-A and trim the length so that the two will butt together. Apply adhesive and glue into place.

5. A secondary seal is applied to the top front (dog leg) portion of the door. Position the seal so that the notched end will encircle the drain hole located on the front of the door. The raised edge of the seal sets flush with the inside of the door. Apply adhesive and secure into place.

1955 passenger side door shown

