

C6DZ-6620530-PR 1966 Falcon Ranchero / 1967 Fairlane Ranchero Door Seal Installation



HELPFUL TIPS

Experience has shown us that by mocking up the door seals into position before permanently applying them allows you to check the orientation and the fit of the seals to the door.

Make sure that the seal is not twisted when beginning to insert the push-in fasteners. Removal of the fasteners to make corrections after installation may cause the fasteners to break.

This type of door seal does not require adhesive for application.



4140 Concord Parkway So., Concord, NC 28027
(704) 786-8139 email: info@dennis-carpenter.com
www.dennis-carpenter.com

TO INSTALL DOOR SEALS

Remove the old door seals and broken plastic push-in fasteners from the doors. Clean the doors where the seals are to be attached with a degreaser / wax remover solution.

1. By using the diagrams on the right determine the left and right side door seals.

Find the 7" section of specially molded rubber of the seal. It is made of rubber that is more dense than the foam rubber and has one fastener attached to it. This will be referred to as the starting point.

As shown in the diagram, all of the push-in fasteners are used on the hinge side, bottom, and latch side of the door.

2. Beginning at the bottom of the vent window of the passenger door, push in the plastic fastener of the specially molded rubber section of the door seal into the first hole located below the vent window on the door.

3. Continue inserting the fasteners down the hinge side of the door, along the bottom then up the lock side until the last fastener is secured just below the window frame.

4. The portion of the door seal without fasteners is held into position by gently tucking it into the metal channel of the door frame using a blunted screw driver or a narrow dull edged putty knife. Use caution so as not to cut the seal with the tool.

5. Once the door seal has been completely inserted into the metal channel slide it back and forth to settle it in and to remove any kinks.

6. Repeat the same operation as described above for the driver's side door seal installation.

